

Power Supply	220~240V/1ph/50Hz
Heating Capacity(Max.)(A7/6°C, W30/35°C)	
Heating Capacity(kW)	6.07(2.63~9.10)
Power Input(kW)	1.19(0.54~2.28)
Coefficient of Performance	5.10(4.20~5.40)
Heating Capacity(Max.)(A7/6°C, W47/55°C)	
Heating Capacity(kW)	5.99(2.99~8.19)
Power Input(kW)	1.87(1.03~2.92)
Coefficient of Performance	3.02(2.90~3.46)
Cooling Capacity(Max.)(A35/24°C, W12/7°C)	
Cooling Capacity(kW)	5.00(1.38~5.70)
Power Input(kW)	1.77(0.67~2.44)
Energy Efficiency Ratio	2.82(2.03~3.20)
ErP Level(Outlet Water Temp. at 35°C/55°C)	A+++ / A+++
Rated Power Input(kW)	3.6
Rated Current Input(A)	15.0
Refrigerant	R290
Rated Water Flow(m ³ /h)	1.00
Water Pressure Drop(kPa)	20
Fan Quantity	1
Fan Motor Type	DC Inverter
Compressor	DC Inverter
Circulating Pump	Inverter Type/Built-in
IP Class	IPX4
Max. Outlet Water Temp. (°C)	75
Operating Temp. Range(Heating Mode)(°C)	-25~45
Operating Temp. Range(Cooling Mode)(°C)	16~45
Sound Pressure at 1m Distance(dB(A))	43(39~51)
Sound Pressure at 3m Distance(dB(A))	35(32~44)
Water Piping Connections(inch)	G1
Net Weight(kg)	140
Gross Weight(kg)	160
Net Dimensions(L*D*H)(mm)	1270*460*955
Packed Dimensions(L*D*H)(mm)	1300*500*1090
Note: The data above is for reference only. Please refer to the nameplate on	